

# ACE3400 N-Channel Enhancement Mode MOSFET

### Description

The ACE3400 is the N-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application such as cellular phone and notebook computer power management and other battery powered circuits, and low in-line power loss are needed in a very small outline surface mount package.

### Features

- 30V/5.4A, R<sub>DS(ON)</sub>=38mΩ@V<sub>GS</sub>=10V
- 30V/4.6A, R<sub>DS(ON)</sub>=42mΩ@V<sub>GS</sub>=4.5V
- 30V/3.8A, R<sub>DS(ON)</sub>=55mΩ@V<sub>GS</sub>=2.5V
- Super high density cell design for extremely low R<sub>DS(ON)</sub>
- Exceptional on-resistance and maximum DC current capability

### Application

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter


#### **Absolute Maximum Ratings**

Parameter		Symbol	Max	Unit
Drain-Source Voltage		$V_{\text{DSS}}$	30	V
Gate-Source Voltage		$V_{GSS}$	±12	V
	<b>T<sub>A</sub>=25</b> ℃	l <sub>D</sub>	4.5	A
	<b>T</b> <sub>A</sub> <b>=70</b> °C		3.5	
Pulsed Drain Current		I <sub>DM</sub>	25	А
Continuous Source Current (Diode Conduction)		I <sub>S</sub>	1.7	А
Power Dissination	<b>T</b> <sub>A</sub> =25°℃	P <sub>D</sub>	2.0	W
	<b>T<sub>A</sub>=70</b> ℃		1.3	
Operating Junction Temperature		TJ	150	°C
Storage Temperature Range		T <sub>STG</sub>	-55/150	°C
Thermal Resistance-Junction to Ambient		R <sub>θJA</sub>	90	°C/W



# ACE3400 N-Channel Enhancement Mode MOSFET

## **Ordering information**





# ACE3400 N-Channel Enhancement Mode MOSFET

#### Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD. As sued herein:

- Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and shoes failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
- 2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ACE Technology Co., LTD. http://www.ace-ele.com/