



ACE74528UI

High-Efficiency 1A Continuous, 28V Input Synchronous

Description

The ACE74528UI is high-efficiency, high frequency synchronous step-down DC-DC regulator ICs capable of delivering up to 1A continuous output currents. The ACE74528UI family operate over a wide input voltage range from 4.5V to 28V and integrate main switch and synchronous switch with very low $R_{DS(ON)}$ to minimize the conduction loss.

ACE74528UI adopts the COT architecture to achieve fast transient responses for high step-down applications and high efficiency at light loads. In addition, it operates at pseudo-constant frequency of 500kHz under heavy load conditions to minimize the size of inductor and capacitor.

Features

- Low $R_{DS(ON)}$ for internal switches (top/bottom) 130m Ω /90m Ω , 1A DC current
- 4.5-28V input voltage range
- High-Efficiency Synchronous-Mode
- Internal soft start limits the inrush current
- Over Current protection
- Thermal shutdown
- Green package: SOT23-6 is pin compatible.

Applications

- Portable Navigation Device
- Set Top Box
- Portable TV
- LCD TV



ACE74528UI

High-Efficiency 1A Continuous, 28V Input Synchronous

Absolute Maximum Ratings

Stresses beyond those listed under “Absolute Maximum Rating” may cause permanent damage to the device. These are stress ratings only and functional operation of the device at these or any other condition beyond those indicated in the operational sections of the specifications is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Parameter		Rating	Unit
Supply Voltage (V+ – V-)		30	V
EN, LX Voltage		$V_{IN}+0.3$	V
FB, BS Voltage		4	V
Power Dissipation, PD @ $T_A = 25^{\circ}\text{C}$		0.6	W
Package Thermal Resistance	θ_{JA}	170	$^{\circ}\text{C/W}$
	θ_{JC}	130	
Storage Temperature Range		-65 to 150	$^{\circ}\text{C}$
Junction Temperature Range		150	$^{\circ}\text{C}$
Lead Temperature Range		260	$^{\circ}\text{C}$
HBM ESD, JESD22-A114	VIN Pin	± 1	kV
	Other Pins	± 2	

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended Operating conditions are specified to ensure optimal performance to the datasheet specifications.

Parameter	Rating	Unit
Supply Voltage	4.5 to 28	V
Junction Temperature Range	-40 to 125	$^{\circ}\text{C}$
Ambient Temperature Range	-40 to 85	$^{\circ}\text{C}$




ACE74528UI

High-Efficiency 1A Continuous,28V Input Synchronous

Ordering information

ACE74528UI XX + H





ACE74528UI

High-Efficiency 1A Continuous,28V Input Synchronous

Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD. As sued herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.