



ACE24AC02A3D

Two-wire Serial EEPROM

Description

The ACE24AC02A3D is 2048 bits of serial Electrical Erasable and Programmable Read Only Memory, commonly known as EEPROM. They are organized as 256 words of 8 bits (1 byte) each. The devices are fabricated with proprietary advanced CMOS process for low power and low voltage applications. A standard 2-wire serial interface is used to address all read and write functions. Our extended VCC range (1.7V to 5.5V) devices enables wide spectrum of applications.

Features

- Low voltage and low power operations:
VCC = 1.7V to 5.5V, Temperature range (-40°C to 85°C).
- ACE24AC02A3D with 3 bits device address, the devices are suitable for all application.
(For use of 5 pins package, the device address A2, A1 and A0 bits must be set to zero)
- 16 bytes page write mode.
- Partial page write operation allowed.
- Internally organized: 256 × 8 (2K).
- Standard 2-wire bi-directional serial interface.
- Schmitt trigger, filtered inputs for noise protection.
- Self-timed programming cycle (5ms maximum).
- 1 MHz (2.5-5V), 400 kHz (1.7V) Compatibility.
- Automatic erase before write operation.
- Write protect pin for hardware data protection.
- Additional write lockable page (Identification page).
- High reliability: typically 1,000,000 cycles endurance.
- 100 years data retention.
- Standard DIP-8/SOP-8/MSOP-8/TSSOP-8/UDFN8/SOT-23-5/TSOT-23-5 packages.

Absolute Maximum Ratings

Operating temperature	-40°C to 85°C
Storage temperature	-50°C to 125°C
Input voltage on any pin relative to ground	-0.3V to VCC + 0.3V
Maximum voltage	6.5V
ESD protection on all pins	>4000V

Notice:

Stresses exceed those listed under “Absolute Maximum Rating” may cause permanent damage to the device. Functional operation of the device at conditions beyond those listed in the specification is not guaranteed. Prolonged exposure to extreme conditions may affect device reliability or functionality.




ACE24AC02A3D

Two-wire Serial EEPROM

Ordering Information

ACE24AC02A3D XX + X H





ACE24AC02A3D

Two-wire Serial EEPROM

Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD. As sued herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ACE Technology Co., LTD.
<http://www.ace-ele.com/>