



# **ACE724517RT**

## **17V 2A 500KHz ECOT Sync Step-Down Regulator**

### **Description**

The ACE724517RT is a high frequency, synchronous, rectified, step-down converter with internal power MOSFETs. It offers a very compact solution to provide a 2A continuous output current over a wide input supply range, with excellent load and line regulation. ECOT control operation provides very fast transient response and easy loop design as well as very tight output regulation.

The ACE724517RT requires a minimal number of readily available, external components and is available in a space saving SOT-23-6 package.

### **Features**

- Wide 4.5V to 17V Operating Input Range
- 2A Continuous Output Current
- 500KHz Switching Frequency
- ECOT Mode Control with Fast Transient Response
- Built-in Over Current Limit
- Built-in Over Voltage Protection
- PFM Mode for High Efficiency in Light Load
- Internal Soft-Start
- 110mΩ/70mΩ Low RDS(ON) Internal Power MOSFETs
- Output Adjustable from 0.6V
- No Schottky Diode Required
- Short Protection with Hiccup-Mode
- Integrated internal compensation
- Thermal Shutdown
- Available in SOT-23-6 package
- -40°C to 85°C Temperature Range

### **Application**

- Digital Set-top Box (STB)
- Tablet Personal Computer (Pad)
- Flat-Panel Television and Monitor
- Wi-Fi Router / AP
- Digital Video Recorder (DVR)
- Portable Media Player (PMP)
- Cable Modem / XDSL
- General Purposes



# ACE724517RT

## 17V 2A 500KHz ECOT Sync Step-Down Regulator

### Absolute Maximum Ratings <sup>Note (1)(2)</sup>

Item	Min	Max	Unit
VIN voltage	-0.3	18	V
EN voltage	-0.3	18	V
SW voltage	-3	19	V
SW voltage (<10 ns transient)	-5	19	V
BS voltage (to SW)	-0.3	6.5	V
FB voltage	-0.3	6	V
Power dissipation <sup>(3)</sup>	Internally Limited		
Operating junction temperature, TJ	-40	150	°C
Storage temperature, Tstg	-55	150	°C
Lead Temperature (Soldering, 10sec.)		260	°C

Note (1): Exceeding these ratings may damage the device.

Note (2): The device is not guaranteed to function outside of its operating conditions.

Note (3): The maximum allowable power dissipation is a function of the maximum junction temperature,  $T_{J(MAX)}$ , the junction-to-ambient thermal resistance,  $R_{\theta JA}$ , and the ambient temperature,  $T_A$ . The maximum allowable power dissipation at any ambient temperature is calculated using:  $P_{D(MAX)} = (T_{J(MAX)} - T_A)/R_{\theta JA}$ . Exceeding the maximum allowable power dissipation causes excessive die temperature, and the regulator goes into thermal shutdown. Internal thermal shutdown circuitry protects the device from permanent damage. Thermal shutdown engages at  $T_J=160^{\circ}\text{C}$  (typical) and disengages at  $T_J= 130^{\circ}\text{C}$  (typical).

### Recommended Operating

Item	Min	Max	Unit
Operating Junction Temperature <sup>Note (1)</sup>	-40	125	°C
Operating Temperature Range	-40	85	°C
Input Voltage $V_{IN}$	4.5	17	V
Output Current	0	2	A

Note(1): All limits specified at room temperature ( $T_A=25^{\circ}\text{C}$ ) unless otherwise specified. All room temperature limits are 100% production tested. All limits at temperature extremes are ensured through correlation using standard Statistical Quality Control (SQC) methods. All limits are used to calculate Average Outgoing Quality Level (AOQL).



# ACE724517RT

## 17V 2A 500KHz ECOT Sync Step-Down Regulator

### ESD Ratings

Item	Description	Value	Unit
$V_{(ESD-HBM)}$	Human Body Model (HBM) ANSI/ ESDA/JEDEC JS-001-2014 Classification, Class: 2	$\pm 2000$	V
$V_{(ESD-CDM)}$	Charged Device Mode (CDM) ANSI/ESDA/JEDEC JS-002-2014 Classification, Class: C0b	$\pm 200$	V
$I_{LATCH-UP}$	JEDEC STANDARD NO.78E APRIL 2016 Temperature Classification, Class: I	$\pm 150$	mA

### Thermal Information

Item	Description	Value	Unit
$R_{\theta JA}$	Junction-to-Ambient Thermal Resistance <sup>Note (1)(2)</sup>	105	°C/W
$R_{\theta JC(TOP)}$	Junction-to-Case (TOP) Thermal Resistance	55	°C/W
$R_{\theta JB}$	Junction-to-Board Thermal Resistance	17.5	°C/W
$\Psi_{JT}$	Junction-to-Top Characterization Parameter	3.5	°C/W
$\Psi_{JB}$	Junction-to-Board Characterization Parameter	17.5	°C/W

Note (1): The package thermal impedance is calculated in accordance to JESD 51-7.

Note (2): Thermal Resistances were simulated on a 4-layer, JEDEC board.




# ACE724517RT

17V 2A 500KHz ECOT Sync Step-Down Regulator

## Ordering Information

ACE724517RT XX + H





# **ACE724517RT**

## **17V 2A 500KHz ECOT Sync Step-Down Regulator**

### Notes

ACE does not assume any responsibility for use as critical components in life support devices or systems without the express written approval of the president and general counsel of ACE Technology Co., LTD. As stated herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ACE Technology Co., LTD.  
<http://www.ace-ele.com/>